



Fleetcool OAT kjølevæske

Bestillingsnr

Fleetcool OAT konsentrat	
5 liter	CC 36137 M
20 liter	CC 36138 M
208 liter	CC 36139 M

Fleetcool OAT premix	
5 liter	CC 36142 M
20 liter	CC 36143 M
208 liter	CC 36144 M



Produsentgodkjenninger

➔ **Fleetcool OAT is designed to meet the following standards and OEM performance requirements:**

- BS 6580:1992
- Case New Holland® MAT 362
- Caterpillar® EC-1 P RR338A, 329, & 330
- Cummins® CES 14603
- DAF® MAT 74002
- Daimler Chrysler MS-9769
- Daimler Truck 48-25960
- Deutz TR 0199-99-1115
- Detroit Diesel® 93K217
- EMD M.I. 1748G & 1796A
- Ford WSS-M97B44-D & WSS-M97B51-A1
- FV R530/2005
- GM-6038M , GM-6277M
- IVECO® 18-1830
- John Deere JDM H24 & 8650-5
- KHD H-LV 01610188
- Komatsu® KES 07.892
- MAN® 324 Si-OAT
- Mercedes DBL 7700.02
- MTU MTL 5048
- Nissan Diesel
- Renault 41-01-001
- Scania TI 02-98 0813 T/B/M sv , 0-89 1027GT EN & TB 1451
- Volkswagen TL774C & TL774F
- Volvo® 20774185 & 1286083
- Waukesha® 4-1974D

